

SC-19



LED 

A value 19" surveillance display with rapid response time, quick signal-switching and robust video support for security and control centre environments.

For a cost-effective surveillance display solution, look no further than the AG Neovo SC-19. A bright, high resolution full colour screen with quick signal-switching and 3ms response time ensures sharp, smooth video playback. Looping BNC video inputs and NTSC/PAL support maximise flexibility for system integration. And with built-in speakers, stylishly slim profile and VESA mountability, the SC-19 will look just as attractive as its amazingly affordable price.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-19

Specifications

SC-19

| | | |
|------------------------------|--|---|
| Panel | Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time | LED-Backlit TFT LCD 19.0" (483mm) SXGA 1280 x 1024 0.294 mm 250 cd/m ² (Typical) 1000:1 (Typical) 170°/160° (Typical) 16.7M 3 ms (GTG) |
| Horizontal Resolution | TV Lines | 550TVL (NTSC), 550TVL (PAL) |
| Frequency (H/V) | | H: 31 kHz - 80 kHz V: 50 Hz - 75 Hz |
| Input | Analogue Digital CVBS S-Video | 15-Pin D-Sub 24-Pin DVI-D BNC x 1 4-Pin mini DIN |
| Out | CVBS | BNC x 1 |
| Audio | Audio In Audio Out Speaker | 3.5mm Audio Line-in 3.5 mm Audio Line-in 1W x 2 |
| Power | Power Supply Power Requirements Consumption | External DC 12V < 25 W (On) < 0.8 W (Off) |
| Plug & Play | VESA | DCC 2B |
| Operating Conditions | Temperature Humidity | 0 °C ~ 40 °C 10% ~ 85% |
| Storage Conditions | Temperature Humidity | -20 °C ~ 60 °C 10% ~ 95% |
| Mounting | VESA FPMPI | Yes (100 x 100mm) |
| Tilt | Tilt | -5° ~ +15° |
| Dimensions | Product (W x H x D) Packaging (W x H x D) | 420 x 408 x 164mm (16.5" x 16.1" x 6.5") 461 x 489 x 164mm (18.1" x 19.3" x 6.5") |
| Weight | Product Weight Packaged Weight | 5.5 kg (12.1 lbs) 5.7 kg (12.5 lbs) |
| Regulation Approval | Certifications & Compliance | UL/CUL, CB, FCC, CE, BSMI, GOST-R, WEEE, RoHS |
| Accessories | Supplied | User manual, power cord, power adaptor, 15-Pin D-Sub cable, audio cable, warranty card |



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI, S-Video, and BNC In/Out

